

System feature:

- Max work depth: 300 msw
- Single video channel (N.2 switchable cameras)
- RS 485 communication link
- Single function gripstick manipulator (on request)
- Powered rotating brush for spot cleaning (on request)
- Seaeye MCT1 brushless magnetically coupled DC thrusters, 4 vectored and 1 vertical thrusters, 13 kgf each
- Auto heading and depth
- 12V, 24V & 48V DC outlets at Vehicle
- Single channel variable intensity of lighting with total output 150W
- Tilt mounted spot led light (on request)
- One high resolution colour camera mounted on tilt platform
- Low light monochrome camera mounted on tilt platform (on request)
- Single channel video overlay cortex (on request)
- One 15 inch JVC high Resolution monitor
- One 10 inch JVC high Resolution monitor
- Two DVD recorders (DVD +R standard)
- Tritech navigation sonar system
- Long distance full optionals spares kit c/w spare 200 m umbilical
- 200 m umbilical (up to 400 m umbilical length available on request)
- Stainless steel launch and recovery garage
- Launch and recovery a-frame c/w electric winch (safe area – on request)
- 3x2x2.5 m. Control Cabin airconditioned (safe area – on request)
- VHF/UF Communications system



Vehicle Specifications:

| | |
|----------------------|-------------------------------|
| Length: | 1000 mm |
| Height: | 500 mm |
| Width: | 600 mm |
| Weight in air: | 62 kg |
| Payload: | 16 kg |
| Thrust forward: | 50 kgf |
| Thrust Lateral: | 28 kgf |
| Thrust Vertical: | 13 kgf |
| Max speed: | 3.5 kts (5,6 km/h) |
| Power Requirements: | 5 KVA Monophase 0/60Hz 220VAC |
| Deck Space Required: | 20 m ² (215 Sqf) |

All particulars believed to be correct but not guaranteed

DNT Offshore Srl - Via G. Bondi, 31 48100 Ravenna - Italy - Phone: +39 0544 685 665 - Fax +39 0544 684 046
www.dntoffshore.com - dnt@dntoffshore.com